






500W MODULE SPORTGROUND DALI SERIES 415V (3 PHASE)

5050 LUMILED SERIES


BMP-5STADV-400-150V-10D4



SPECIFICATIONS	
System Power	500w
Milliamps	2520Ma (184V x 2pcs)
LED type	LUMILED 5050 96Pcs each Module
Lamp Body Material	Powdercoated Galvanised Steel
Colour Temperature	4000k(3000k,5700kopt)
Luminous Flux	67,500 Lumens
Luminous Efficacy	135 Lm/w
CRI	Ra80 (Ra70/90 optional)
Beam Angle	25X25, 40X40, 60X60
Rated Lifespan	>100,000 hours
IP Rating	IP67 Housing , IP68 Modules
Impact rating	IK09
Driver Type	Inventronics Flicker Free ESM-240S150DG x 2pcs
Operating Temperature	-40°C ~ 50°C
Dimmable	PWM Dimming
Test Reports	ISMT,LCP,TM21,LM80, L70
Lamp Dimension	335 x 600 x 220 mm
Net Weight	9.6kg + 2.3kg
Warranty	5 years drivers,10 years Modules
Certification	JAS/ANZ TUV



25x25 B/Angle **BMP-5STADL25-500-1504-10D4**
40x40 B/Angle **BMP-5STAD40-500-1504-10D4**



60x60 B/Angle **BMP-5STAD60-500-15054-10D4**



500W MODULE SPORTGROUND DALI SERIES 415V (3 PHASE)

5050 LUMILED SERIES

BMP-5STADV-400-150V-10D4

For accessories, contact BMP LED via
www.bmpled.com.au/contact

ACCESSORIES




Light Shields
BMP-FL40SHIELD-10



Red Laser pointer
BMP-REDLPOINT-10



Driver Extension Cable
2.0m,5.0m,12.0 lengths
BMP-DEC/2/5/12-10



Birdspikes
0.33m
BMP-BIRDSPIKES-10