




180W 3 MODULE RECESSED CANOPY LIGHT



BMP-3RCAN-180-150V-10

- White
- Grey
- Black




SPECIFICATIONS


System Power	180w
Milliamps	1200Ma
LED type	LUMILEDS 5050 28Pcs each Module
Lamp Body Material	Powdercoated Galvanised Steel
Colour Temperature	5700k(3000k,4000kopt)
Luminous Flux	27,000lumens
Luminous Efficacy	150lm/w
CRI	Ra70 (Ra80/90 optional)
Beam Angle	90x90,60X60,40x40, 90x40
Rated Lifespan	>100,000 hours Modules
IP Rating	IP67 Housing , IP68 Modules
Impact rating	IK09
Driver Type	Moso Flicker Free X6-150M214
Operating Temperature	-40°C ~ 50°C
Dimmable	PWM Dimming
Test Reports	ISMT,LCP, TM21, LM80, L70
Lamp Dimension	650 x 650 x 110 mm
Net Weight	13.2kg
Warranty	5 years driver, 10 years Modules
Certification	JAS/ANZ TUV




90x90 B/Angle
BMP-3RCAN90-180-15057-10



120x120 B/Angle
BMP-3RCAN120-180-15057-10



90x40 B/Angle
BMP-3RCAN2211-180-15057-10



Tunnel Module
BMP-3RCAN2123-180-15057-10



180W 3 MODULE RECESSED CANOPY LIGHT

BMP-3RCAN-180-150V-10

For accessories, contact BMP LED via
www.bmp-led.com.au/contact

ACCESSORIES



Driver Extension Cable
2.0m, 5.0m, 12.0 lengths
BMP-DEC/2/5/12-10

