






60W 1 MODULE MODULAR HIBAY SERIES


BMP-HBV-60-150V-10




SPECIFICATIONS	
System Power	60w
Milliamps	1200Ma
LED type	LUMILEDS 5050 28Pcs each Module
Lamp Body Material	Powdercoated Galvanised Steel
Colour Temperature	5700k(3000k,4000kopt)
Luminous Flux	9,000lumens
Luminous Efficacy	150lm/w
CRI	Ra70 (Ra80/90 optional)
Beam Angle	90x90,90x40,120X120,
Rated Lifespan	>100,000 hours Modules
IP Rating	IP67 Housing , IP68 Modules
Impact rating	IK09
Driver Type	Moso Flicker Free X6-075M062
Operating Temperature	-40°C ~ 50°C
Dimmable	PWM Dimming
Test Reports	ISMT,LCP, TM21, LM80, L70
Lamp Dimension	360 x 200 x 95 mm
Net Weight	4.8kg
Warranty	5 years driver, 10 years Modules
Certification	JAS/ANZ TUV




90x90 B/Angle
BMP-HB90-60-150V-10



120x120 B/Angle
BMP-HB120-60-150V-10



90x40 B/Angle
BMP-HB2211-60-150V-10
Pallet racking isles



150x50 B/Angle
BMP-HB2123-60-150V-10

See modular Photometric for additional beam Angles



60W 1 MODULE MODULAR HIBAY SERIES


BMP-HBV-60-150V-10

For accessories, contact BMP LED via
www.bmpled.com.au/contact


ACCESSORIES



Driver Extension Cable
2.0m,5.0m,12.0 lengths
BMP-DEC/2/5/12-10



Birdspikes
0.33m
BMP-BIRDSPIKES-10



BMP-BRACKET250-10