



200W 4 DALI MODULE RECESSED CANOPY LIGHT



BMP-RCAN-200-150V-10D

- White
- Grey
- Black




SPECIFICATIONS


System Power	200w
Milliamps	1000Ma
LED type	LUMILEDS 5050 28Pcs each Module
Lamp Body Material	Powdercoated Galvanised Steel
Colour Temperature	5700k(3000k,4000kopt)
Luminous Flux	32,000lumens
Luminous Efficacy	160lm/w
CRI	Ra70 (Ra80/90 optional)
Beam Angle	90x90,60X60,40x40, 90x40
Rated Lifespan	>100,000 hours Modules
IP Rating	IP67 Housing , IP68 Modules
Impact rating	IK09
Driver Type	Moso Flicker Free
Operating Temperature	-40°C ~ 50°C
Dimmable	Dali
Test Reports	ISMT,LCP, TM21, LM80, L70
Lamp Dimension	650 x 650 x 110 mm
Net Weight	13.2kg
Warranty	5 years driver, 10 years Modules
Certification	JAS/ANZ TUV




90x90 B/Angle
BMP-RCAN90-200-15057-10D



120x120 B/Angle
BMP-RCAN60-200-15057-10D



90x40 B/Angle
BMP-RCAN2211-200-15057-10D



Tunnel Module
BMP-RCAN2123-200-15057-10D



200W 4 DALI MODULE RECESSED CANOPY LIGHT

BMP-RCAN-200-150V-10D

For accessories, contact BMP LED via
www.bmp-led.com.au/contact

ACCESSORIES



Driver Extension Cable
2.0m, 5.0m, 12.0 lengths
BMP-DEC/2/5/12-10

