



# 240W 4 MODULE RECESSED CANOPY LIGHT



BMP-RCAN-240-150V-10

- White
- Grey
- Black




## SPECIFICATIONS


System Power	240w
Milliamps	1200Ma
LED type	LUMILEDS 5050 28Pcs each Module
Lamp Body Material	Powdercoated Galvanised Steel
Colour Temperature	5700k(3000k,4000kopt)
Luminous Flux	36,000lumens
Luminous Efficacy	150lm/w
CRI	Ra70 (Ra80/90 optional)
Beam Angle	90x90,60X60,40x40, 90x40
Rated Lifespan	>100,000 hours Modules
IP Rating	IP67 Housing , IP68 Modules
Impact rating	IK09
Driver Type	Moso Flicker Free X6-240M229
Operating Temperature	-40°C ~ 50°C
Dimmable	PWM Dimming
Test Reports	ISMT,LCP, TM21, LM80, L70
Lamp Dimension	650 x 650 x 110 mm
Net Weight	13.2kg
Warranty	5 years driver, 10 years Modules
Certification	JAS/ANZ TUV




90x90 B/Angle  
BMP-RCAN90-240-15057-10



120x120 B/Angle  
BMP-RCAN120-240-15057-10



90x40 B/Angle  
BMP-RCAN2211-240-15057-10



Tunnel Module  
BMP-RCAN2123-240-15057-10



# 240W 4 MODULE RECESSED CANOPY LIGHT

BMP-RCAN-240-150V-10

For accessories, contact BMP LED via  
[www.bmp-led.com.au/contact](http://www.bmp-led.com.au/contact)

## ACCESSORIES



Driver Extension Cable  
2.0m, 5.0m, 12.0 lengths  
BMP-DEC/2/5/12-10

