






200W 4 MODULE STREETLIGHT LIGHT SERIES

BMP-STREETM-200-150V-10



- White
- Grey
- Black

SPECIFICATIONS	
System Power	200w
Milliamps	1000Ma
LED type	LUMILEDS 5050 28Pcs each Module
Lamp Body Material	Aluminium Alloy
Colour Temperature	5700k,4000k,3000k
Luminous Flux	32,050lumens
Luminous Efficacy	160lm/w
CRI	Ra70(Ra80/90 Optional)
Beam Angle	TYPE I, II , III , IV , V
Light Distribution Curve	Various
Rated Lifespan	>100,000 hours Modules
IP Rating	IP66 Housing , IP68 Modules
Impact rating	IK08
Driver Type	Moso Flicker Free X6-240M229
Operating Temperature	-40°C ~ 50°C
Dimmable	PWM Dimming
Test Reports	TM21,LM80,L70
Lamp Dimension	785x330x155 mm
Net Weight	10.8kg
Warranty	5 years driver, 10 years Modules
Certification	JAS/ANZ TUV



Type II (Most Common)
BMP-STREET2-200-150V-10

See next page for other distributions








200W 4 MODULE STREETLIGHT LIGHT SERIES

BMP-STREETM-200-150V-10

For accessories, contact BMP LED via www.bmpled.com.au/contact

ACCESSORIES



Type I

BMP-STREET1-200-150V-10

Type II

BMP-STREET2-200-150V-10
(Most Common)

Type III


BMP-STREET3-200-150V-10

Type IV


BMP-STREET4-200-150V-10

Type V

BMP-STREET5-200-150V-10




Streetlight pole Adaptor
Black/Grey/White Options
BMP-STREETAD-10(B/G/W)



3 Pin Phot Cell
Pe Cell and base
BMP-STREETCELL3-10



Driver Extension Cable
2.0m,5.0m,12.0 lengths
BMP-DEC/2/5/12-10



Birdspikes
0.33m
BMP-BIRDSPIKES-10